

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

		Subclass
	Class	ISSUE CLASSIFICATION

PATENT NUMBER

U.S. UTILITY Patent Application

M.S.	O.I.P.E.		PATENT DATE
SCANNED <u>LM3</u>	Q.A.		

APPLICATION NO. 09/893898	CONT/PRIOR F	CLASS 327 333	SUBCLASS 024206	ART UNIT 28107	EXAMINER Rettendorf
------------------------------	-----------------	--------------------------------	--------------------	-------------------	------------------------

APPlicants

Yoshinobu Sasaki

TITLE

High-frequency circuit device

PTO-2040
12/99

ISSUING CLASSIFICATION

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig. 	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				NOTICE OF ALLOWANCE MAILED	
	(Assistant Examiner)	(Date)			
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____ _____ _____				ISSUE FEE	
	(Primary Examiner)	(Date)		Amount Due	Date Paid
<input type="checkbox"/> The terminal ___ months of this patent have been disclaimed. _____ _____				ISSUE BATCH NUMBER	
	(Primary Examiner)	(Date)			

WARNING:

WARNING: The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-436A
(Rev. 6/99)

FILED WITH: DISK (CRF) FICHE CD-ROM
(Attached in pocket on right inside flap)